

# MICROMASTER® 430 AC Inverters

## The Simple Standard to Save Energy


The **MICROMASTER 430** inverter is a variable torque drive designed for industrial variable speed fan and pump applications. The MM430 is an easy-to-use inverter characterized by linear and quadratic V/Hz control capability. User-oriented functionality includes commissioning macro, flying restart, manual/auto mode, energy consumption monitoring, pump staging, and bypass logic control. The MM430 can interface with input voltage ranges from 380V to 480V in power ranges from 10 to 350hp.

### Main Characteristics

- Ready to install<sup>1</sup> and operate right out of the box.
- Simple commissioning macro to easily make changes in factory programming.
- Side-by-side mounting.
- Six fully programmable isolated digital inputs.
- Two scalable analog inputs, can also be used as 7th and 8th digital inputs.
- Two fully programmable analog outputs.
- Three fully programmable relay outputs.
- Silent motor operation is possible when using high switching frequencies.
- Complete inverter and motor protection.

### Performance Features


- Latest IGBT technology.
- Digital microprocessor control.



<sup>1</sup> Factory pre-programmed for 4 pole NEMA or IEC motors; digital input control for switching the inverter "on," "fault reset," and analog setpoint speed control.



- Programmable, multi-point V/Hz curve, linear V/Hz control, quadratic V/Hz control.
- High grade PID controller for process control with energy saving mode.
- Load torque detection for dry well/belt break detection.
- Integrated pump cascade control logic (motor staging).
- Automatic restart following power failure or fault.
- Integrated bypass control logic.
- Binary Connector (BiCo) technology.
- Fast, repeatable digital input response time.
- Programmable acceleration/ deceleration, 0s to 650s.
- Multi-curve, adjustable ramp smoothing.
- Fast current limit (FCL) for trip free operation.
- Standard RS-485 serial port.



### Siemens — Your Best Choice

The **MICROMASTER MM430** product line is integrated into the Siemens family of drives, motor, and programmable controller automation products. All products are backed by Siemens worldwide service and support capability. Contact your local Siemens sales office or distributor to get the complete story of the MICROMASTER MM4 drives.

**SIEMENS**

## Variant Independent Options

### Basic Operator Panel–2 (BOP–2)

With the BOP–2, individual parameter settings can be made. Values and units are shown on a 5-digit display. One basic BOP–2 operator panel can be used for several inverters and can be directly mounted on the inverter or in an enclosure door using an optional mounting kit. The BOP–2 includes Hand/Auto selection for control/setpoint changeover.



### PROFIBUS Communication Module

With the optional PROFIBUS communication module, PROFIBUS–DP operation is possible up to 12MB.

In addition, the BOP–2 can be attached to the front of the PROFIBUS module giving a form-fitting, operational display. The PROFIBUS module can also be powered from an external 24V supply to ensure the node remains active when power is removed from the inverter.

### DeviceNet Communication Module

Optional DeviceNet Module is used for networking inverters to the DeviceNet fieldbus system. Maximum transmission rate of 500 kbaud is possible.

### DriveMonitor and / or Starter Commissioning Tool

DriveMonitor and / or Starter is a Windows®-based, commissioning software package for MICROMASTER inverters. Parameter lists can be read, altered, stored, entered, and printed.

## Technical Specifications – MM430 AC Inverter

Input voltage and power ranges 380 V to 480 V 3 AC ± 10%	Variable torque rated 10hp to 350hp			
Input frequency	47 Hz to 63 Hz			
Output frequency	0 Hz to 650 Hz			
Power factor	>98%			
Inverter efficiency	96% to 97%			
Overload capability	1.1 x rated output current for 60 seconds (every 300 seconds) or 1.4 x rated for 3 seconds (every 60 seconds).			
Inrush current	Less than rated input current			
Control method	Programmable V/Hz curve; Linear V/Hz curve; Quadratic V/Hz curve			
PWM frequency	4kHz standard, adjustable 2 kHz to 16 kHz (in 2 kHz steps)			
Fixed frequencies	15, programmable			
Skip frequency bands	4, programmable			
Setpoint resolution	0.01 Hz digital 0.01 Hz serial 10 bit analog			
Digital inputs	6 fully programmable, isolated digital inputs plus the option for up to eight; selectable PNP/NPN			
Analog input	2 for setpoint or PID input (0–10V, 0–20mA, or (AIN1)) scalable, or for use as 7th and 8th digital inputs			
Relay output	3 configurable 30 V DC/5 A (resistive), 250 V AC/2 A (inductive); 2 Form C, 1 NO			
Analog output	2, programmable (0/4 mA to 20 mA)			
Serial interfaces	RS-485, optional RS-232, optional PROFIBUS, optional DeviceNet, optional CANbus			
Electromagnetic compatibility	Optional EMC filters to EN 55 011, Class A or Class B, Inverter with internal filter Class A available			
Braking	DC Injection Braking and Compound Braking			
Protection level	IP 20			
Temperature range	–10°C to +40°C (14°F to 104°F)			
Storage temperature	–40°C to +70°C (–40°F to 158°F)			
Humidity	95% Relative Humidity – non-condensing			
Operational altitudes	up to 3,300 ft (1,000 m) without derating			
Protection features	<ul style="list-style-type: none"> <li>• under-voltage</li> <li>• over-voltage</li> <li>• stall prevention</li> <li>• overload</li> <li>• ground faults</li> <li>• locked motor</li> <li>• short circuits</li> <li>• motor over-temperature I2t, PTC Thermistor or Klaxon Thermostat</li> <li>• inverter over-temperature</li> <li>• parameter PIN protection</li> </ul>			
Standards	UL, cUL, c-Tick			
CE Mark	Conformity with CE low voltage directive 73/23/EEC and the EMC directive 89/336/EEC with filtering			
Dimensions and weights (Without gland plate)	Frame size	W x H x D (mm)	W x H x D (in.)	Weight (lbs)
	C	185 x 245 x 195	7.3 x 9.6 x 7.7	12.1
	D	275 x 520 x 245	10.8 x 20.5 x 9.6	35
	E	275 x 650 x 245	10.8 x 25.6 x 9.6	44
	F w/o filter	350 x 850 x 320	13.8 x 33.5 x 12.6	123
	FX	326 x 1400 x 356	12.83 x 55.12 x 14.06	254
	GX	326 x 1533 x 545	12.83 x 60.35 x 21.46	388

Siemens is a registered trademark of Siemens AG. Product names mentioned may be trademarks or registered trademarks of their respective companies. Specifications are subject to change without notice.